

ACOUSTICS

Introduction Technology

Design

The Range

Home Cinema Accessories Specifications

5020

Experience all the scale and power of your favourite music without letting your loudspeaker dominate your room. The 5020 standmounting speaker by Q Acoustics will put your right in the heart of the music without putting itself at the heart of your space - its understated looks are at odds with the assertive and convincing nature of its sound. A pair of 5020 speakers + a pair of speaker stands = endless audio gratification.







Satin White

Satin Black

Santos Rosewood



Holme Oak

Acoust	rics				5000 SERIES Introduction Technology Design The Range Home Cinema Accessories Specifications
		5010	5020	5040	_
	Bass unit	1 x 110 mm (4.5 in)	1 x 125 mm (5.0 in)	2 x 125 mm (5.0 in)	
	Treble unit	1 x 25 mm (1.0 in)	1 x 25 mm (1.0 in)	1 x 25 mm (1.0 in)	
	Frequency response (-6dB)	56Hz - 30 kHz	53 Hz - 30 kHz	39 Hz - 30 kHz	
	Nominal impedance	6 Ω	6 Ω	6 Ω	_
	Minimum impedance	3.3 Ω	3.3 Ω	3.0 Ω	_
	Sensitivity (2.83V @ 1kHz)	86.3 dB/w/m	87.9 dB/w/m	91.5 dB/w/m	_
	Recommended amplifier power	15-90 W	25-100 W	25-150 W	_
	Crossover frequency	2.5 kHz	2.5 kHz	2.5 kHz	_
	Effective volume	5.0 L	6.8 L	27 L	_
	Dimensions HxWxD (per loudspeaker)	264 x 160 x 263 mm (10.4 x 6.3 x 10.4 in)	284 x 180 x 293 mm (11.2 x 7.1 x 11.5 in)	Inc spikes and stabiliser: 967 x 361 x 293 mm (38.1 x 14.2 x 11.5 in)	
	Weight (per loudspeaker)	5.6 kg (12.3 lbs)	7.0 kg (15.4 lbs)	18.0 kg (39.7 lbs)	